Customer approval :



Specification:

1). Driving: Duty:1/240,Bias:1/19,VEE:-16.5V,V0:-17.2V,VDD:5.0V.
2). Viewing direction: 6 o'clock
3). Display mode:FFSTN/Negative/Transmissive
4). Operating temp:-20°C~+70°C
5). Storage temp: -30°C~+80°C
6). Control IC:NO
7). Backlight: White CCFL
8). dimensions with mark "*" are important with mark "()" are referenced
9). All the raw materials are RoHS compliant

PIN	1	2	3	4	5	6	7	8	9	10	11	12
CONNECTION	V0	VEE	D0	D1	D2	D3	DISP	VSS	VDD	CP	LP	FLM

REV	REVISION RECORD	DATE
A	FIRST ISSUE	2017/09/01
B		
C		
D		

深圳市三元晶科技有限公司
ShenZhen TCCLCD HI- Tech Co., Ltd.

MODEL NO. 模组型号	M155BVA-5KFM4-B6WIP		GENERAL TOL: 未注公差	± 0.3
APPROVED BY 审核	CHECKED BY 检查	DRAWING BY 绘图	PAGE: 页面	UNIT: 单位
Liu 2017/09/01	Francis 2017/09/01	Luoxian 2017/09/01	1 OF 1	mm
			PROJECTION 三角法	