


Customer approval :



SCALE: 20:1

COM&SEG layout

1. Driving: Duty:1/240, Bias:1/12, VDD:5.0V
2. VIEWING DIRECTION: 6 O'CLOCK
3. Display mode: FSTN/Positive/Transflective
3. Operating temp.: -10°C~+60°C
4. Storage temp.: -20°C~+70°C
5. Control IC: RA8835AP3N
6. BACKLIGHT Color: Blue
7. DIMENSIONS WITH MARK "x" ARE IMPORTANT WITH MARK "y" ARE REFERENCED
8. All the raw materials are RoHS compliant

P1N	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
SYMBOL	GND	VDD	V0	WR	RD	CS	A0	RES	D0	D1	D2	D3	D4	D5	D6	D7	NC	YOUT	BLA	BLK

REV	REVISION RECORD	DATE	 深圳市三元晶科技有限公司 Shenzhen TCC LCD Hi-Tech Co., Ltd
A0	First issue	5-21	

MODEL NO.	SYG320240L1V10-5C1G1LN6R8-B5NZF	GENERAL TOL:	± 0.3
模组型号		未注公差	

			PAGE: 1 OF 1 UNIT: m 単位
	APPROVED BY	CHECKED BY	DRAWING BY

PROJECTION		角 法	三 角
			