



DOT SIZE

SPECIFICATION:

- 1). Driving: Duty:1/16, Bias:1/5, VDD:5.0V, VLCD:4.5V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Positive/Transflective/YG
- 4). Operating temp.: -20°C~+70°C
- 5). Storage temp.: -30°C~+80°C
- 6). Control IC: SPLC780D1-001-C(Or Compatible)
- 7). BACKLIGHT: EDGE,YG
- 8). DIMENSIONS WITH MARK "*" ARE IMPORTANT WITH MARK "()" ARE REFERENCED
- 9). All the raw materials are RoHS compliant

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	BLA	BLK

REV	REVISION RECORD	DATE
A0	First issue	11-19



深圳市三元晶科技有限公司
Shenzhen TCC LCD Hi-Tech Co., Ltd.

DRAWING NO.	SYB1602C1V10-5C10YL5-BSN	GENERAL TOL:	± 0.2
APPROVED BY	CHECKED BY	DRAWING BY	UNIT: mm
		Jequil	PAGE
		2010/11	1/1