



SPECIFICATION:

- 1). Driving: Duty: 1/2, Bias: 1/2, V_{dd}: 3.3V, V_o: 4.8V, V_{out}: 6.0V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Positive/Transflective/(Y/G)
- 4). Operating temp.: -20°C~+70°C
- 5). Storage temp.: -30°C~+80°C
- 6). Control IC: ST7920-0B (or Compatible)
- 7). BACKLIGHT: Edge,LED Y/G
- 8). DIMENSIONS WITH MARK "*" ARE IMPORTANT WITH MARK "<" ARE REFERENCED
- 9). All the raw materials are RoHS compliant

1	2	3	4	5	6	7	8	9	~	16	17	18	19	20
BLK	BLA	VSS	VDD	NC	RS(cs)	R/W(stn)	E(sck)	DB0	~	DB7	PSB	RST	VO	VOUT

REVISION RECORD		REV
First issue		V2.0



深圳市三元晶液显示科技有限公司
Shenzhen TCC LCD Hi-Tech Co., Ltd

DRAWING NO. SYB12864AZKV20-3C11YL3N2R-B5NH		GENERAL TOL: ±0.2	
APPROVED BY	CHECKED BY	DRAWING BY	UNIT: mm
		Luoxian	PAGE
		2012/02/27	1/1