



SPECIFICATION:

- 1). Driving: Duty:1/64, Bias:1/9, Vdd:5.0V, Vlcd:7.5V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Negative/Transmissive/Grey
- 4). Operating temp.:0°C~+50°C
- 5). Storage temp.: -10°C~+60°C
- 6). Control IC: SNB6400G
- 7). BACKLIGHT: White
- 8). DIMENSIONS WITH MARK "*" ARE IMPORTANT WITH MARK "()" ARE REFERENCED
- 9). All the raw materials are RoHS compliant

1	DB7	2	DB6	3	DB5	4	DB4	5	DB3	6	DB2	7	DB1	8	DB0	9	E	10	R/W
11	V0	12	VDD	13	VSS	14	CS2	15	CS1	16	VOUT	17	RST	18	BLA	19	BLK	20	

REV	REVISION RECORD	DATE	MODEL NO.		CHECKED BY		DRAWING BY		GENERAL TOL:		UNIT:
A			SYB19264AV11-3C9K1LN3R		检查		绘图		± 0.2		mm
B			SYB19264AV11-3C9K1LN3R		检查		绘图		± 0.2		mm
C			SYB19264AV11-3C9K1LN3R		检查		绘图		± 0.2		mm
D			SYB19264AV11-3C9K1LN3R		检查		绘图		± 0.2		mm



深圳市三元晶液晶显示科技有限公司
Shenzhen TCC LCD Hi-Tech Co., Ltd.

